



**Europäisches  
Patentamt**

**European  
Patent Office**

**Office européen  
des brevets**

NL030256

**Bescheinigung**

**Certificate**

**Attestation**

Die angehefteten Unterlagen stimmen mit der ursprünglich eingereichten Fassung der auf dem nächsten Blatt bezeichneten europäischen Patentanmeldung überein.

The attached documents are exact copies of the European patent application described on the following page, as originally filed.

Les documents fixés à cette attestation sont conformes à la version initialement déposée de la demande de brevet européen spécifiée à la page suivante.

**Patentanmeldung Nr.    Patent application No.    Demande de brevet n°**

03100688.5

Der Präsident des Europäischen Patentamts;  
Im Auftrag

For the President of the European Patent Office

Le Président de l'Office européen des brevets  
p.o.

**R C van Dijk**

**THIS PAGE BLANK (USPTO)**

**THIS PAGE BLANK (USPTO)**



Anmeldung Nr:  
Application no.: 03100688.5  
Demande no:

Anmeldetag:  
Date of filing: 18.03.03  
Date de dépôt:

Anmelder/Applicant(s)/Demandeur(s):

Koninklijke Philips Electronics N.V.  
Groenewoudseweg 1  
5621 BA Eindhoven  
PAYS-BAS

Bezeichnung der Erfindung/Title of the invention/Titre de l'invention:  
(Falls die Bezeichnung der Erfindung nicht angegeben ist, siehe Beschreibung.  
If no title is shown please refer to the description.  
Si aucun titre n'est indiqué se référer à la description.)

Backlight, liquid crystal apparatus comprising such backlight and method for  
operating such apparatus

In Anspruch genommene Priorität(en) / Priority(ies) claimed / Priorité(s)  
revendiquée(s)  
Staat/Tag/Aktenzeichen/State/Date/File no./Pays/Date/Numéro de dépôt:

Internationale Patentklassifikation/International Patent Classification/  
Classification internationale des brevets:

G02F/

Am Anmeldetag benannte Vertragsstaaten/Contracting states designated at date of  
filing/Etats contractants désignées lors du dépôt:

AT BE BG CH CY CZ DE DK EE ES FI FR GB GR HU IE IT LU MC NL  
PT SE SI SK TR LI

Backlight, liquid crystal apparatus comprising such backlight and method for operating such apparatus

The present invention relates to a backlight for a liquid crystal display, comprising a light source and a lightguide to be illuminated by said light source from an edge of said lightguide, the lightguide comprising a plurality of adjacent areas for illumination of corresponding parts of a liquid crystal panel.

5 The invention also relates to a liquid crystal display apparatus comprising such a backlight.

The invention also relates to a method for operating such a liquid crystal display apparatus wherein the light guide comprises  $n$  areas and the liquid crystal panel comprises  $n$  parts that correspond to said  $n$  areas of the backlight, wherein  $n \geq 2$ .

10 US patent application No. 2002/0003522 discloses a liquid crystal display method to reduce motional artifacts. In the method, a liquid crystal display apparatus is used which comprises a lighting part divided into a plurality of areas, the lighting/non-lighting of each of which can be controlled. Thereto either the method of direct illumination by providing electroluminescent illumination of each area is used, or the lighting of the areas is controlled by a liquid crystal shutter arranged between the backlight part and a liquid crystal panel. In the latter case, the shutter is e.g. divided into four light stripes. Each stripe may be made transmissive or non-transmissive for the light provided by the lighting part of the backlight. Here, this light comes from one light source which is provided at an edge of the lightguide of the backlight.

15 A drawback of this liquid crystal display apparatus is the fact that only one light source is used for all lighting parts at the same time. This implies that a more or less large part of the light is lost when one or more of the shutter parts are non-transmissive. This indicates an undesirably low energy efficiency.

20

25

An object of the invention is to provide a backlight for a liquid crystal display, which has an improved energy efficiency.

The object is achieved with a backlight according to claim 1.

The presence of independently controllable light sources for each of the areas of the lightguide offers the possibility to illuminate only those areas which need to be illuminated. The backlight according to the invention ensures a minimum energy consumption. In particular in the case of a method which is useful in reducing motion artifacts this offers great advantages. This will be elucidated below.

Another advantage of the backlight according to the invention is that it is now possible to change the light source for a particular area of the lightguide, should this be required or desirable.

It is noted that the cited US patent application offers the possibility of separate light sources for each area of the lightguide. However, thereto it is necessary to incorporate electroluminescent light sources in the backlight itself. This is disadvantageous in view of the complex method to manufacture such a backlight with built-in light sources. Furthermore, it is not possible to change the light sources afterwards. To the contrary, the backlight according to the invention is provided with a light source which illuminates the lightguide from a side thereof, the so-called edge-lit illumination technique. Since this is a much simpler and more versatile technique, this is the arrangement considered in this application.

Preferably, the plurality of areas consists of a first area and a second area having a common edge. This is the simplest configuration of the backlight according to the invention, however still having all the advantages thereof. Hence it can be manufactured and operated in the simplest possible way. Furthermore, in the case that this backlight is operated such that only one of the areas is illuminated while the other is dark, and vice versa, the average power consumption may be made more or less constant, while the power density is lower than in cases in which there are more than two areas.

Advantageously, the light source of each of the two areas is provided at an edge opposite said common edge. Not only does this offer even more design possibilities, but in particular it is now possible to provide the light sources at those edges having the largest dimension and/or the shortest distance to the common edge. This ensures that the power density within the light source may be held as low as possible. Furthermore, it is now possible to cool the light source on more sides thereof.

Although the light source of the backlight according to the invention is not particularly limited, preferably at least one light source comprises a LED or a LED based light source. LEDs have a very short rise and fall time, of the order of 10 ns. This ensures a very quick response to control signals, and a high average illuminance level. Furthermore, it

is possible to divide the area to be lit into many small subareas, which are to be lit for only a very short time. Hence the rise and fall of the lighting should be very quick. Moreover, LEDs have a high energy efficiency and a high density of illumination, a very long life and do not suffer much from being switched on and off many times.

5           The LED based light sources include unpackaged LEDs and LEDs in various packages, such as single package LEDs and stripline LEDs. The latter package offers a number of LEDs in line, in a transparent tube. Especially this type of LED based light source is ideally suited for use in the backlight according to the invention. It is to be noted that throughout this application, the term LED includes LED based light source.

10           However, other light sources, such as cathode fluorescent light source are not excluded. In many cases, in particular lower switching frequencies etc., these kinds of light also sources provide a high density of illumination and have very compact dimensions.

15           The invention also relates to a liquid crystal display apparatus comprising a liquid crystal panel and a backlight therefor according to the invention. Such a liquid crystal display apparatus is a compact display means having the versatility and power economy that is provided by this invention.

20           Advantageously, the liquid crystal display apparatus further comprises first means for writing image data in the liquid crystal panel, and second means for independently controlling an illumination of the areas of the backlight. Although the presence of the first means and/or second means in the liquid crystal display apparatus is not necessary, it is advantageous to combine the functions in the apparatus in order to obtain a compact and more or less stand-alone unit. It is also possible, however, to control the liquid crystal panel and/or one or more light sources with other means, not comprised in the display apparatus.

25           The first means for writing image data in the liquid crystal panel may for example consist of a control circuit connected to a plurality of scanning lines and signal lines perpendicular thereto. At the intersections of scanning lines and signal lines a plurality of pixels are arranged, corresponding to said intersections. Switching elements corresponding to the pixels are provided, which, on receiving an appropriate signal, will switch the transmittance of the liquid crystal(s) associated with each pixel.

30           The second means for independently controlling an illumination of the areas of the backlight may e.g. comprise a control circuit for controlling the light sources of the areas of the backlight. Advantageously, the first means and second means are controllable simultaneously. This will be elucidated further below.

The invention also relates to a method for operating a liquid crystal display apparatus according to the invention, wherein the lightguide comprises  $n$  areas, and the liquid crystal panel comprises  $n$  parts that correspond to said  $n$  areas of the backlight, wherein  $n \geq 2$ ; the method comprising repeating the following steps:

- 5       -           selecting one of the parts of the liquid crystal panel corresponding to one of the areas of the backlight;
- writing image data in said part, while said area is not illuminated and at least one of the remaining areas of the backlight is illuminated.

A preferred embodiment of the method is claimed in claim 9.

10       An advantage of the method according to the invention is that it offers a simple yet elegant method to reduce motion artifacts problems when displaying moving images on the liquid crystal display apparatus. In a more general sense, the method according to the invention will be referred to as the "pseudo scanning backlight method".

15       It is to be understood that selection of a part of the LCD panel and lighting of the corresponding area need not be strictly simultaneous actions. Of course, they should however follow each other quicker than the writing action.

20       Please note that it is possible to write only in those parts of the panel, or even only that part, in which the image changes in any desired order. If the image in a certain part does not change, image data need not be rewritten to said part. Clearly, in this situation the advantage of the presence of multiple light sources is prominent, as the parts with the constant image may be illuminated continuously at an appropriate intensity, which is advantageous for the light source and the smoothness of the image. However, in many addressing modes, every consecutive part is addressed, whatever the change in the image. In that case, each part of the panel is selected consecutively and data are written in it, with the corresponding illumination of the areas corresponding to the other parts.

25       In the method, use is made of a liquid crystal display apparatus according to the invention, and the liquid crystal panel is divided in a number of parts, that correspond to the different areas of the backlight. It is to be noted that this division need not be physical, but may be considered as grouping of pixels into certain subsets. In a comparable fashion, the backlight need not be divided into physically separated areas, but rather, the light sources  
30       used are able to illuminate predominantly one of the areas. Thereto, the lightguide and the light sources are designed such that each light source predominantly but not exclusively illuminates an area of the backlight and hence a corresponding part of the liquid crystal panel.



The phrase "not exclusively" indicates that a smooth transient is allowed to prevent discontinuous lighting in the display.

Motion artifacts are a well-known problem in LCD (liquid crystal display)-based displays when they are used for displaying fast moving images and/or video

information. These motion artifacts are a result of the combination of three factors:

(1) the mode of addressing the LCD pixels and their subsequent (slow) relaxation to the newly addressed state;

(2) the backlighting of the LCD panel;

(3) the properties of the human eye and the vision centre in the human brain.

In particular, continuous backlighting of the LCD panel causes the remnants of the first image to be still visible while a subsequent image is being written to the LCD panel, due to the slow relaxation of the LCD pixels. Furthermore, the human eye and brain are able to follow motion continuously, while an image of a movement on an LCD consists of a contiguous series of in itself steady state images.

The method according to the invention ensures that the part of the LCD panel that is being addressed is not illuminated. In other words, the lighting of the backlight areas and the addressing of the panel parts have a phase shift with respect to each other.

The invention will now be elucidated by means of non-limiting examples, with reference to the drawings, in which:

Fig. 1a and 1b are plan views of two embodiments of the backlight according to the invention;

Fig. 2 is a side elevation view of a liquid display apparatus with the backlight of Fig. 1b; and

Fig. 3a and 3b represent a control voltage for the light sources of the backlight of Fig. 1b.

Fig. 1a shows a plan view of a backlight according to the invention, in which 1a and 1b are two light sources, 2a and 2b are two lightguide areas, which are divided by a line of division 3, represented by a dashed line.

4 represents the direction in which consecutive pixels of an LCD panel are to be addressed, when such panel is to be used together with the backlight.

In the figure, light sources 1a and 1b are shown as two separate units. In practice, this may be arranged as one larger unit having separately controllable parts, e.g. one large group of LEDs which may be controlled separately.

The light sources have preferably small dimensions, because in many applications the overall dimensions of the backlight are small. Hence, advantageously the light sources 1a and 1b comprise LEDs, for example white light LEDs or groups of coloured LEDs, e.g. with complementary colours. Advantageously, the LEDs are present in the form of stripline LEDs. Other light sources are not excluded, such as cathode fluorescent light sources, or electroluminescent light sources.

The light sources 1a and 1b are optically coupled to lightguide areas 2a and 2b. The lightguide may be any lightguide structure known in the art. In the drawing, the lightguide is divided into two parts 2a and 2b by means of a line of division 3. It is to be noted that this line need not correspond to any physical division but rather indicates an imaginary line which indicates the boundary between an area 2a which is predominantly lighted by the light source 1a and an area 2b which is predominantly lighted by the light source 1b.

Although in the drawing the lightguide is divided into two areas 2a and 2b, it is to be noted that the lightguide may in principle be divided into any number of mutually parallel areas. In that case a correspondingly larger number of light sources must be present. These light sources could for example be present in the form of a continuous row of light sources. Advantageously, the light sources of adjacent areas are present on opposite sides of the areas. This offers the advantage of improved cooling of the light sources.

The areas 2a and 2b are divided up according to the direction 4 in which an image is built up in an LCD panel to be used with the backlight. In this way it is ensured that each line of pixels in the panel which is being addressed is within one and the same area of the backlight.

Fig. 1b shows a plan view of a different arrangement of light sources 1a and 1b and lightguide areas 2a and 2b.

The lightguide areas 2a and 2b correspond to the arrangement according to Fig. 1a. However, now the light sources 1a and 1b are arranged on that edge of the lightguide part 2a, 2b, respectively, which is located opposite the common edge thereof, which is located at the line of division 3. An advantage of this arrangement is that the distance between the light sources 1a, 1b and the line of division, which indicates the maximum distance for the light to travel, is smaller than in the case according to Fig. 1a. This means

that the light intensity of the light source may be lower, which offers a wider choice of light sources.

Fig. 2 shows a side elevation view of a liquid crystal display apparatus with a backlight according to the invention.

5           The apparatus shown consists of light sources 1a and 1b which can illuminate respective lightguide areas 2a and 2b, divided by line of division 3. The light sources are controlled by means of light source control means 7, connected to the respective light sources by means of first connection cable 8.

10           5a and 5b are a first and second part of a liquid crystal panel, divided by means of second line of division 6. The panel parts 5a and 5b are addressed by means of panel addressing means 9, and connected thereto by means of second connection cable 10.

15           The lightguide area 2a is to illuminate panel part 5a, and the lightguide area 2b is to illuminate panel part 5b. To ensure a good correspondence of illumination, the second line of division 6 should be aligned with line of division 3. For both lines of division 3, 6 holds that they may be physical lines of division but may also be considered to be imaginary boundary lines in one lightguide, LCD panel respectively.

20           The panel addressing means 9 serve to address the pixels or crystals of the display panel 5a, 5b. According to most addressing modes, pixels are addressed in the form of consecutive lines. Such lines preferably lie completely within one panel part. In that case, the lines are perpendicular to the plane of the drawing. Although the addressing mode by means of consecutive lines is preferred, other modes of addressing are not excluded, such as random addressing.

25           The light source control means 7 serve to independently operate light sources 1a and 1b. Thereto, the means 7 may be provided with an energy source, e.g. mains, and a switch. This switch may comprise electronic circuitry to enable synchronization of the switching action with the addressing of the panel. Preferably, the light source control means 7 and the panel addressing means 9 are coupled.

Fig. 3a and 3b show control signals for the light sources 1a and 1b of the liquid crystal display apparatus according to Fig. 2.

30           In the figures, a voltage over the light sources is represented. Herein Von represents a voltage in a lit state, and 0 represents a non-lit state of the light sources. Depending on the working principle of the light sources, the voltage may be replaced by a current, etc.

Fig. 3a represents the signal over the light source 1a, whereas 3b represents the signal over light source 1b, both in the same timeframe. In the timeframe, between times  $t = T$  the light source 1a is off, whereas light source 1b is lit. During this time, according to the method for operating the apparatus according to the invention, the liquid crystal panel part 1a is being addressed. During the time between  $t = T$  and  $t = 2T$ , the first light source 1a is lit whereas the second light source 2b is off. During said time, the liquid crystal panel part 5b is being addressed. From the time  $t = 2T$  this cycle of alternating lighting of the light sources and addressing the panel parts is repeated with a period of  $2T$ , with a phase shift of  $180^\circ$ , or  $(360^\circ/\text{number of areas})$  in general.

In this example of the method according to the invention, the number of light sources, areas and parts is 2. The method also works with higher numbers. The essence is that during addressing of a particular part of the liquid crystal display panel, the light source for illuminating said part is off, whereas all or a part of the other parts of the liquid crystal display panel are lit by their respective light sources.

In the figures 3a and 3b, the duty cycle of each light source is 50%. It may however be advantageous to have a duty cycle between 40 and 60% because of the following. Liquid crystals have a non-zero relaxation time, in order to further improve the definition of the displayed image, it may be advantageous to illuminate the panel part only from the time that the liquid crystals have relaxed to their steady state. In most cases, e.g. with addressing frequencies of 60 Hz, a relaxation time of about  $0,1 T$  will be sufficient, i.e. a minimum duty cycle of 40%. Although this means the occurrence of a completely black panel during  $0,1 T$  twice during each cycle, the properties of human vision cause a smooth image to be perceived.

Likewise, if the relaxation time of the pixels is short enough to not pose any problems, or e.g. the images to be displayed show less or no motion, the duty cycle may be up to 60%. Since there is now some overlap between the lighting of both areas and panels, the resulting image is even smoother.

However, duty cycles of up to 50% are preferred, because in that case the peak power for operating the backlight is between 1 and 1,25 times the average power. This makes the power electronics for the backlight less complicated and cheaper than in the case of duty cycles of more than 50%.

## CLAIMS:

1. A backlight for a liquid crystal display, comprising a light source and a lightguide to be illuminated by said light source from an edge of said lightguide, the lightguide comprising a plurality of adjacent areas for illumination of corresponding parts of a liquid crystal panel, characterized in that each of said areas is provided with an independently controllable light source for illuminating substantially said area.
2. The backlight according to claim 1, characterized in that the plurality of areas consists of a first area and a second area having a common edge.
3. The backlight according to claim 2, characterized in that the light source of each area is provided at an edge opposite said common edge.
4. The backlight according to any of the preceding claims, characterized in that at least one light source comprises a LED or a LED based light source.
5. The backlight according to any of the preceding claims, characterized in that at least one light source comprises a cathode fluorescent light source.
6. A liquid crystal display apparatus comprising a liquid crystal panel and a backlight therefor according to any of the preceding claims.
7. The liquid crystal display apparatus according to claim 6, characterized in that it further comprises first means for writing image data in the liquid crystal panel, and second means for independently controlling an illumination of the areas of the backlight.
8. A method for operating a liquid crystal display apparatus according to any of claims 6-7, wherein the lightguide comprises  $n$  areas, and the liquid crystal panel comprises  $n$  parts that correspond to said  $n$  areas of the backlight, wherein  $n \geq 2$ , the method comprising repeating the following steps:

- selecting one of the parts of the liquid crystal panel corresponding to one of the areas of the backlight;
- writing image data in said part while said area is not illuminated and at least one of the remaining areas of the backlight is illuminated.

5

9. The method according to claim 8, wherein a backlight is selected having two areas of equal dimensions, and wherein the step of writing image data to one of the parts of the liquid crystal panel that corresponds to one of the areas requires a time  $T$ , wherein during said step the other area of the backlight is illuminated during a time of between  $0.8 \cdot T$  and  $T$ .

**ABSTRACT:**

The invention provides a backlight for an LCD display, an LCD display apparatus with such a backlight, and a method for operating the apparatus.

5 The backlight is divided into a plurality, preferably two, areas, each with their own separate light source. The LCD display apparatus comprises said backlight and an LCD panel divided into parts corresponding to the areas.

The backlight and the LCD apparatus according to the invention provide a means for suppressing motion artifacts while ensuring versatile and power economic operation.

10 A method for operating said apparatus includes lighting only those areas of the backlight which correspond to those parts of the LCD panel which are not being addressed at that time.

Fig. 2

**THIS PAGE BLANK (USPTO)**